

## Brass Service Saddles for PVC Pipe

### Brass Service Saddles

Brass Service Saddles are designed for use on PVC pipe, and give a positive watertight seal with full circle support to the PVC pipe without cracking or distorting the pipe. Pressure capabilities of these high quality saddles equal but do not exceed the pressure rating of the PVC pipe up to 200 psig.

Brass Service Saddles are made to fit both IPS (Steel O.D.) and AWWA C900 (Ductile Iron O.D.) PVC pressure pipe. All saddles have cast IPS or C900 Pipe O.D. range identification. Tapped outlets are color coded: Green for AWWA CC tap threads and Yellow for FNPT tap threads.

#### Specifications:

- 1. Body and Strap:** 85-5-5-5 Cast Brass per ASTM B62
- 2. Bolts:** Silicon Bronze with slotted hex head on 1½" through 8" saddles and ¾" hex head on 10" and 12" saddles.
- 3. Gasket:** EPDM o-ring bonded to o-ring groove
- 4. Outlet Sytle Color Code:** Green for AWWA threads and Yellow for FNPT pipe threads.



### Brass Saddles for IPS & C-900 PVC PIPE

NOM. PIPE SIZE	PIPE O.D.	PRODUCT NUMBERS							
		OUTLET SIZE & THREAD TYPE							
		¾" CC	¾" IP	1" CC	1" IP	1½" CC	1½" IP	2" CC	2" IP
1½"	1.90	54267		NA	NA	NA	NA	NA	NA
2"	2.38	54430	54429	54450	54461	NA	NA	NA	NA
2½"	2.88	54650	NS	54652	54648	NA	NA	NA	NA
3"	3.50	54756	54758	54776	54832	NS	NS	NA	NS
4"	4.50	55490	55492	55480	55521	55528	NS	55535	NS
4"	4.80	55478	55493	55481	55522	55529	NS	55536	NS
6"	6.63	56320	56321	56341	56351	56342	NS	56345	NS
6"	6.90	56362	56322	56363	NS	56343	NS	56367	NS
8"	8.63	57100	57091	57105	57095	57108	NS	57110	NS
8"	9.05	57124	NS	57125	57094	57109	NS	57115	NS
10"	10.75	57841	NS	57840	NS	NS	NS	NS	NS
10"	11.10	57842	NS	57843	NS	NS	NS	NS	NS
12"	12.75	58348	NS	58582 1	NS	58500	NS	58583 1	NS
12"	13.20	58580	NS	58582	NS	58581	NS	NS	NS

#### NOTES:

- Items designated with NS are non-stock. Please call your local Team EJP sales office for information.
- Items designated with NA are not available.
- Outlet taps are available up to 2" in both FNPT and AWWA (CC) threads in saddle sizes 4" thru 12".
- For cold water service only.