Backflow Prevention Devices I-5

Double Check Backflow Preventers & Strainers

Series 709 Double Check Valve Assembly Sizes 2½" – 10"



709 Shown with Optional NRS RW Valves

Features:

- Resilient Wedge gate valve shut-offs UL/FM approved
- FDA approved epoxy coated check valves (inside and out)
- · Removable bronze seats
- · Stainless steel internal parts
- · Maximum flow with low pressure drop
- Simple design for easy maintenance
- · No special tools required

Series 709 2½"-10" sizes provide backflow protection in cross-connection control and containment. These assemblies are suitable for supply pressures up to 175 PSI and water temperatures to 110°F.

The assemblies are tested and certified under the following standards for reduced pressure backflow preventers; ASSE No. 1015, AWWA C510-92, CSA B64.5, FCCCHR of USC Manual Section 10, U.L. Classified File No. EX3185. Listed by IAPMO (UPC): SBCCI (Standard Plumbing Code).

NOTE:

 See back of Table of Contents for abbreviations used in this section. **Cast Iron Strainers**



Model 77F-D-FDA

The Series 77F-D-FDA "Y" type strainers have a stainless steel screen* and a cast iron body with two coats of fusion-bonded epoxy applied to both the interior and exterior. FDA approved for potable water and food contact. Ideal for liquid service where a non-corrosive construction/clean cosmetic appearance is required.

The Series 77F-D-FDA is available in standard 125 lb. or 250 lb. faced and drilled flanges. 125 lb. flanges are suitable for supply pressures up to 200 PSI at 100°F WOG.

* A wide variety of screen opening sizes are available. Please contact your local Team EJP sales office for assistance.

	PRODUCT NUMBER			
SIZE	709 NRS RW	709 OS&Y RW	EPOXY CTD. STRAINER	
21/2"	51308 1	51308	51307	
3"	51322 1	51322	51320	
4"	51326	51326 1	51327	
6"	51331	51331 1	51332	
8"	51336	51336 1	51337	
10"	51341	51341 1	51343	

Refer to MBS, Section T for Backflow Installation and Testing Services

Backflow Prevention Devices I-6

Double Check Backflow Preventers

MasterSeries 850 Double Check Assembly



For use in all nonhealth hazard (nontoxic) connections including: irrigation systems, fire sprinkler systems, in-plant commercial and industrial plumbing systems.

	SIZE	PRODUCT NUMBER
DCBF	1/2"	51237 1
PREVENTER	3/4"	51241
850DC	1"	51253 1
	1½"	51266
	2"	51289

MasterSeries 856 Double Check Detector Assembly



For use in fire sprinkler/standpipe/distribution systems requiring detection of unauthorized water use (nontoxic).

DCBF	SIZE	PRODUCT NUMBER
DETECTOR	3"	51317 2
ASSEMBLY	4"	51324
856 OS&Y	6"	51329
	8"	51334

Refer to MBS, Section T for Backflow Installation and Testing Services

Phone: 800-EJP-24HR (357-2447) • Fax: 207-582-5637