Locators M-6

Pipe, Cable & Magnetic Locators

MAC-51BX Magnetic & Dual Frequency Pipe & Cable Locator



Lets you switch between HF & LF modes "on the fly"

Receiver/Transmitter Applications

With the cable locator function, underground telephone, utility and CATV cables, metallized warning tapes and ferrous/nonferrous pipes can be traced using inductive and/or conductive modes.

Receiver Only Applications

With the magnetic locator function, buried manhole covers, water meters, valves and valve boxes, corner markers, marker magnets etc. — any object that has a magnetic field — can be precisely located.

Accessories

Accessories supplied with the MAC-51BX include an earphone jack, a spare batteries holder and a conductive cable assembly with ground stake.

Features:

- Two active frequencies for pipe, cable and line tracing
- Passive operation for locating iron and steel targets and energized 50/60Hz power lines
- Inductive and conductive signal coupling
- Extra heavy duty clips and cable
- · Peak and null operation for precise locating
- · Discrete sensitivity settings
- Receiver supplied with two environmentally friendly 9-volt lithium batteries
- Piezoelectric speaker
- 45° depth measurement
- Patented HeliFlux® Sensors
- Modular construction
- 3-year warranty

DESCRIPTION	PRODUCT NUMBER
MAC-51BX Mag. & Cable Locator	60145
MAC-51BX Inductive Clamp	60146

Options: MT-2 Transmitter is for non-metalic pipe.

Model GA-52CX



The Model GA-52CX HeliFlux® Magnetic Locator is unsurpassed for locating objects such as shutoff valves, manhole covers and other iron objects covered by deep layers of snow and/or soil.

The instrument functions by detecting the magnetic field of the object. Ice, snow, water, etc., do not affect its performance.

Because the instrument detects the magnetic field of iron objects, it can detect these items at substantially greater range than conventional metal detectors.

DESCRIPTION	PRODUCT NUMBER
GA-52CX Locator w/Case	60150 1

Features:

- Enhanced target definition
- Unsurpassed detection range
- Piezoelectric speaker
- · Clear, sharp detection signal pinpoints the target
- No response to aluminum, brass, or copper
- Ease of operation reduces search time
- With experience, user can distinguish between small pieces of scrap iron and actual targets
- 40-hours operation (intermittent usage) on two economical 9-volt batteries
- Modular construction
- High performance components
- Weather protected controls
- Rugged lightweight carrying case
- Patented HeliFlux® sensors
- 7-year warranty