

Valves and Tapping Sleeves C-10

Resilient Wedge Flanged Valves

NRS Flanged Valve



NRS (non rising stem) valves are Resilient Wedge style. Bodies range in sizes 2" thru 24" in ductile iron construction, rated at 250 psi working pressure for AWWA valves. NRS valves are typically used for municipal water systems, fire protection systems and wastewater applications. 2" square nut or wheel handle operators are furnished with valves.

OS&Y Flanged Valve



OS&Y (outside stem and yoke) Resilient Wedge Valves are approved at 250 psi for DI. Generally used in pumping stations and fire protection systems where visual indication is required to determine if the valve is open or closed, the OS&Y gate valve is furnished with wheel handle operators.

SIZE (in.)	DIR. TO OPEN	PRODUCT NUMBERS	
		NRS	OS&Y
2	OR	NA	38993 1
	OL	NA	38993
2	OR	38992	38994 1
	OL	38991	38994
3	OR	NA	39021
	OL	NA	39022
3	OR	39007 01	39022 1
	OL	39007 1	39022 2
4	OR	NA	39034 01
	OL	NA	39034
4	OR	39031 11	39034 11
	OL	39031 1	39034 1
6	OR	NA	39051 01
	OL	NA	39051
6	OR	39047 11	39051 11
	OL	39047 1	39051 1
8	OR	NA	39073 01
	OL	NA	39073
8	OR	39087 11	39073 11
	OL	39087 1	39073 1
10	OR	NA	39093
	OL	NA	39094
10	OR	39106 6	39094 01
	OL	39106 5	39094 1
12	OR	NA	39114 01
	OL	NA	39114
12	OR	39116	39113 1
	OL	39117	39113
16	OR	39132 1	NS
	OL	39132	NS

NOTES:

- All open left flanged valves meet or exceed AWWA C509 and C515 and are UL listed and FM approved.
- For features and specifications on specific models of Resilient Wedge Valves refer to pages C-1 thru C-4.
- **Larger sizes available upon request.**