

Gas Pipe & Fittings T-18

800-EJP-24 HR

The slip-type design protects the service from downward pressure. The box absorbs the pressure from above. If all the downward adjustment is used and additional pressure causes the box to collapse further, the bell area will collapse before damaging the service. This is a SAFE installation.

Because boxes are easily adjusted to grade level, no need to dig when grade changes. Simply step-on to push down or pry it up to raise. There are dimples in the lower tube that put tension on the upper tube which prevents the box from settling. The upper tube has a full throat and unobstructed opening to operate the key.

Boxes are molded from superior grade ABS plastic to prevent rust, rot or corrosion. Cast iron lids, marked "Gas", are available with optional vent holes. Curb boxes feature one-piece locking lid to prevent tampering or from it being lost. Tracer wire holes and tube extensions are also available.

There are two different cast iron rings available; one for off-road and one for in-road use.

SHORT SPEC:

Meets D.O.T. requirement 192.181

2" Curb Box

Features

- Heavy-duty flange top with iron collar
- Adjustable range of 30⁵/₈" to 46"
- Bell to fit 1" Nordstrom valves
- Yellow lid with ³/₈" vent hole



Plastic Valve & Curb Boxes

4" and 6" Valve Boxes

Features

- Available in 1¹/₂" or 5" cast iron flange
- A 6", 9" or 12" bell on lower tube
- Adjustable range of 29" to 42" or 31" to 44"
- Support for 2", 3", 4" or 6" Nordstrom valves
- Yellow lid with ³/₈" vent hole



NOTE: Other options and variations are available, please contact your local EJP sales office for more information.